



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative resistive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SDL

G-Snack Design Twelve (XII) Master

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	SDL
DIMENSIONS H x W x D (mm)	1830* x 1290 x 900
WEIGHT (NET - Standard machine without options)	410 Kg
NO. OF SELECTIONS PER SHELF	12 (6 + 6)
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 84
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	E (Cat. 2) F (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1811 (Cat. 2) 2329 (Cat. 3) 2455 (Cat. 4)

* With adjustable feet

OPTIONAL

SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
7TH SHELF
FRONT GLASS PROTECTION
LOCK PROTECTION
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR
CO2 COOLING UNIT AVAILABLE



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative resistive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SDX

G-Snack Design Ten (X) Master

TECHNICAL SPECIFICATIONS

	SDX
DIMENSIONS H x W x D (mm)	1830* x 1125 x 845
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	F (Cat. 2) E (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1969 (Cat. 2) 2253 (Cat. 3) 2293 (Cat. 4)

* With adjustable feet

OPTIONAL

SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
7TH SHELF
FRONT GLASS PROTECTION
LOCK PROTECTION
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR
CO2 COOLING UNIT AVAILABLE



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative resistive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SC8

G-Snack Design Eight (VIII) Master

TECHNICAL SPECIFICATIONS

SC8

DIMENSIONS H x W x D (mm)	1830* x 980 x 845
WEIGHT (NET - Standard machine without options)	310 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	E (Cat. 2) F (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1704 (Cat. 2) 2133 (Cat. 3) 2114 (Cat. 4)
ENERGY CLASS (HC-R290)	G (Cat. 2) G (Cat. 3) G (Cat. 4)
ENERGY CONSUMPTION - kWh/annum (HC-R290)	2337 (Cat. 2) 2787 (Cat. 3) 2589 (Cat. 4)

* With adjustable leveling screw

*** The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

SPEEDY LIFT
DUO SYNCHRO SPIRAL (NEW)
DOUBLE SPIRAL MOTOR
DUO DIVIDER
KIT SANDWICH / BAGUETTE
7TH SHELF
FRONT GLASS PROTECTION
LOCK PROTECTION
WALL/FLOOR FIXING KIT
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
BRANDING
CUSTOMIZED CABINET COLOUR



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative resistive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SC6

G-Snack Design Six (VI) Master

TECHNICAL SPECIFICATIONS

SC6

DIMENSIONS H x W x D (mm)	1830* x 830 x 845
WEIGHT (NET - Standard machine without options)	275 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	550 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	F (Cat. 2) F (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1877 (Cat. 2) 2213 (Cat. 3) 2716 (Cat. 4)

* With adjustable feet

*** The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- 7TH SHELF
- FRONT GLASS PROTECTION
- LOCK PROTECTION
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR