



Your cravings at your fingertips

A highly inter-active and customizable touch display to boost your sales

Enhance your profits and engage customers by providing them with the latest technologies applied to the touch screen on new SandenVendo vending machine.

A top-notch touch screen display equipped with multi-selection, a feature so attractive and user-friendly that will induce customers to want purchase more. Further, providing the useful nutritional insights, specific brand promotions will drive customer attention with intuitive marketing tools. An advanced control panel that enables you to manage the vending machine effortlessly.

STX

G-Snack Touch Ten (X) Master

TECHNICAL SPECIFICATIONS	STX
DIMENSIONS H x W x D (mm)	1830* x 1125 x 845
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
DISPLAY	7" Touch screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	F (Cat. 2) E (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1969 (Cat. 2) 2253 (Cat. 3) 2293 (Cat. 4)

* With adjustable feet



Your cravings at your fingertips

A highly inter-active and customizable touch display to boost your sales

Enhance your profits and engage customers by providing them with the latest technologies applied to the touch screen on new SandenVendo vending machine.

A top-notch touch screen display equipped with multi-selection, a feature so attractive and user-friendly that will induce customers to want purchase more. Further, providing the useful nutritional insights, specific brand promotions will drive customer attention with intuitive marketing tools. An advanced control panel that enables you to manage the vending machine effortlessly.

ST8

G-Snack Touch Eight (VIII) Master

TECHNICAL SPECIFICATIONS	ST8
DIMENSIONS H x W x D (mm)	1830* x 980 x 845
WEIGHT (NET - Standard machine without options)	310 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
DISPLAY	7" Touch screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	E (Cat. 2) F (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1704 (Cat. 2) 2133 (Cat. 3) 2114 (Cat. 4)
ENERGY CLASS (HC-R290)	G (Cat. 2) G (Cat. 3) G (Cat. 4)
ENERGY CONSUMPTION - kWh/annum (HC-R290)	2337 (Cat. 2) 2787 (Cat. 3) 2589 (Cat. 4)

* With adjustable leveling screw

*** The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.



Your cravings at your fingertips

A highly inter-active and customizable touch display to boost your sales

Enhance your profits and engage customers by providing them with the latest technologies applied to the touch screen on new SandenVendo vending machine.

A top-notch touch screen display equipped with multi-selection, a feature so attractive and user-friendly that will induce customers to want purchase more. Further, providing the useful nutritional insights, specific brand promotions will drive customer attention with intuitive marketing tools. An advanced control panel that enables you to manage the vending machine effortlessly.

ST6

G-Snack Touch Six (VI) Master

TECHNICAL SPECIFICATIONS	ST6
DIMENSIONS H x W x D (mm)	1830* x 830 x 845
WEIGHT (NET - Standard machine without options)	275 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
DISPLAY	7" Touch screen
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	550 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CLASS	F (Cat. 2) F (Cat. 3) F (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1877 (Cat. 2) 2213 (Cat. 3) 2716 (Cat. 4)

* With adjustable feet

*** The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment